

RECEIVED  
CENTRAL FAX CENTER

NOV 28 2006

-2-

**Amendments to the Claims**

Please amend Claims 67, 73, 74, 84-87, 93, 94 and 104-106. The Claim Listing below will replace all prior versions of the claims in the application:

**Claim Listing**

1-66 (Canceled)

67. (Currently Amended) A display system comprising:

a housing having an aperture;

a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture; and

a first polarizer disposed relative to the first side of the display panel, the first polarizer being mounted to be optically aligned with the aperture and mechanically spaced by the housing from the image plane by a distance such that visibility of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer.

68. (Previously Presented) The display system of claim 67 wherein the first polarizer defects can have a size greater than 10 micrometers.

69. (Previously Presented) The display system of claim 67 further comprising a second polarizer disposed relative to the second side of the display.

70. (Previously Presented) The display system of claim 69 wherein the second polarizer is spaced from the image plane by a distance such that second polarizer defects are out of the viewer's depth of focus.

71. (Previously Presented) The display system of claim 70 wherein the first and second polarizer defects can have a size greater than 10 micrometers.

-3-

72. (Previously Presented) The display system of claim 70 in which the second polarizer is mechanically spaced from the image plane by the housing.
73. (Currently Amended) The display system of claim 72 in which the ~~first and~~ second polarizer[[s are]] is mechanically secured by the housing.
74. (Currently Amended) The display system of claim 73 wherein the ~~first and~~ second polarizer[[s are]] is secured within a second receptacle[[s]] in the housing.
75. (Previously Presented) The display system of claim 67 in which the housing comprises a plurality of housing elements.
76. (Previously Presented) The display system of claim 67 further comprising a backlight.
77. (Previously Presented) The display system of claim 76 wherein the backlight comprises a light source, a first diffuser and a second diffuser.
78. (Previously Presented) The display system of claim 77 wherein the light source is a light emitting diode (LED).
79. (Previously Presented) The display system of claim 69 in which the display has a first surface and a second surface, the first polarizer being located at a first distance from the first surface of the display, and the second polarizer being located on the second surface of the display.
80. (Previously Presented) The display system of claim 67 further comprising at least one lens.
81. (Previously Presented) The display system of claim 80 wherein the first polarizer is located between the display and the at least one lens.

-4-

82. (Previously Presented) The display system of claim 67 in which the first polarizer is substantially parallel to the display.
83. (Previously Presented) The display system of claim 67 in which the display has a diagonal that is less than one inch.
84. (Currently Amended) A display system comprising:  
a housing having an aperture;  
a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture;  
a first polarizer disposed relative to the first side of the display panel, the first polarizer being mounted to be optically aligned with the aperture and mechanically secured and spaced by the housing from the image plane by a distance such that visibility of first polarizer defects to a viewer is minimized; and  
a second polarizer disposed relative to the second side of the display panel, the second polarizer mechanically secured and spaced by the housing from the image plane by a distance such that visibility of second polarizer defects to a viewer is minimized, the first and second polarizers being held within respective first and second receptacles in the housing, the first and second receptacles mechanically securing the first and second polarizers.
85. (Currently Amended) A display system comprising:  
a housing comprising a plurality of housing elements and having an aperture;  
a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture; and  
a first polarizer disposed relative to the first side of the display panel, the first polarizer being mounted to be optically aligned with the aperture and mechanically secured and spaced by the housing from the image plane by a distance such that visibility

-5-

of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer.

86. (Currently Amended) A display system comprising:

a housing having an aperture;

a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, the first side having a first surface and the second side having a second surface, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture;

a first polarizer disposed relative to the first side of the display panel, the first polarizer being mounted to be optically aligned with the aperture and mechanically secured and spaced by the housing from the image plane by a first distance from the first surface of the display panel such that visibility of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer; and

a second polarizer disposed relative to the second side of the display panel, the second polarizer being located on the second surface of the display panel.

87. (Currently Amended) A method for assembling a display module comprising:

providing a housing having an aperture;

providing a first polarizer and a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture; and

mounting the first polarizer to be optically aligned with the aperture and, with the housing, mechanically spacing the first polarizer relative to the first side of the display panel by a distance such that visibility of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer.

-6-

88. (Previously Presented) The method of claim 87 further comprising spacing the first polarizer such that the first polarizer defects can have a size greater than 10 micrometers and be out of the viewer's depth of focus.
89. (Previously Presented) The method of claim 87 further comprising disposing a second polarizer relative to the second side of the display.
90. (Previously Presented) The method of Claim 89 further comprising spacing the second polarizer from the image plane by a distance such that second polarizer defects are out of the viewer's depth of focus.
91. (Previously Presented) The method of claim 90 further comprising spacing the first and second polarizers such that the first and second polarizer defects can have a size greater than 10 micrometers and be out of the viewer's depth of focus.
92. (Previously Presented) The method of claim 90 further comprising mechanically spacing the second polarizer from the image plane with the housing.
93. (Currently Amended) The method of claim 92 further comprising mechanically securing the first and second polarizer[[s]] with the housing.
94. (Currently Amended) The method of claim 93 further comprising securing the first and second polarizer[[s]] within a second receptacle[[s]] in the housing.
95. (Previously Presented) The method of claim 87 further comprising providing the housing with a plurality of housing elements.
96. (Previously Presented) The method of claim 87 further comprising providing a backlight.
97. (Previously Presented) The method of claim 96 further comprising providing the backlight with a light source, first diffuser and a second diffuser.

-7-

98. (Previously Presented) The method of claim 97 further comprising providing the backlight with a light source that is a light emitting diode (LED).
99. (Previously Presented) The method of claim 89 in which the display has a first surface and a second surface, the first polarizer being located at a first distance from the first surface of the display, the method further comprising locating the second polarizer on the second surface of the display.
100. (Previously Presented) The method of claim 87 further comprising providing at least one lens.
101. (Previously Presented) The method of claim 100 further comprising locating the first polarizer between the display and the at least one lens.
102. (Previously Presented) The method of claim 87 further comprising positioning the first polarizer substantially parallel to the display.
103. (Previously Presented) The method of claim 87 further comprising providing the display with a diagonal that is less than one inch.
104. (Currently Amended) A method for assembling a display module comprising:
  - providing a housing having an aperture;
  - providing a first polarizer, a second polarizer, and a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture;
  - mounting the first polarizer to be optically aligned with the aperture and, with the housing, mechanically securing and spacing the first polarizer relative to the first side of the display panel by a distance such that visibility of first polarizer defects to a viewer is minimized, and mechanically securing and spacing the second polarizer relative to the second side of the display panel by a distance such that visibility of second polarizer defects to the viewer is minimized, the first and second polarizers being held within

-8-

respective first and second receptacles in the housing, the first and second receptacles mechanically securing the first and second polarizers.

105. (Currently Amended) A method for assembling a display module comprising:
- providing a housing comprising a plurality of housing elements and having an aperture;
  - providing a first polarizer and a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture; and
  - mounting the first polarizer to be optically aligned with the aperture and, with the housing, mechanically securing and spacing the first polarizer relative to the first side of the display panel by a distance such that visibility of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer.
106. (Currently Amended) A method for assembling a display module comprising:
- providing a housing having an aperture;
  - providing a first polarizer, a second polarizer, and a liquid crystal display panel having an image plane, and opposed transparent substrates defining first and second sides of the display panel, the first side having a first surface and the second side having a second surface, at least one substrate being directly mounted to and within the housing so as to position the display panel in optical alignment with the aperture;
  - mounting the first polarizer to be optically aligned with the aperture and, with the housing, mechanically securing and spacing the first polarizer relative to the first side of the display panel by a first distance from the first surface of the display panel such that visibility of first polarizer defects to a viewer is minimized, the first polarizer being held within a first receptacle in the housing, the first receptacle mechanically securing the first polarizer; and
  - disposing the second polarizer relative to the second side of the display panel, the second polarizer being located on the second surface of the display panel.

-9-

107. (Previously Presented) The display system of Claim 67 in which the first polarizer is mechanically spaced by the housing from the image plane and mechanically secured to the housing in a manner where adhesion is not required.
108. (Previously Presented) The display system of Claim 84 in which the first polarizer is mechanically spaced by the housing from the image plane and mechanically secured to the housing in a manner where adhesion is not required.
109. (Previously Presented) The display system of Claim 85 in which the first polarizer is mechanically spaced by the housing from the image plane and mechanically secured to the housing in a manner where adhesion is not required.
110. (Previously Presented) The display system of Claim 86 in which the first polarizer is mechanically spaced by the housing from the image plane and mechanically secured to the housing in a manner where adhesion is not required.
111. (Previously Presented) The method of Claim 87 further comprising mechanically spacing the first polarizer relative to the first side of the display and mechanically securing the first polarizer to the housing in a manner where adhesion is not required.
112. (Previously Presented) The method of Claim 104 further comprising mechanically spacing the first polarizer relative to the first side of the display and mechanically securing the first polarizer to the housing in a manner where adhesion is not required.
113. (Previously Presented) The method of Claim 105 further comprising mechanically spacing the first polarizer relative to the first side of the display and mechanically securing the first polarizer to the housing in a manner where adhesion is not required.
114. (Previously Presented) The method of Claim 106 further comprising mechanically spacing the first polarizer relative to the first side of the display and mechanically securing the first polarizer to the housing in a manner where adhesion is not required.